

Question # 1 of 10 ( Start time: 08:43:07 PM ) Total Marks: 1

Which function is used to create cancel button event of dialog box \_\_\_\_\_.

Select correct option:

OnInitCancel()

**OnClickCancel()**

CancelClick()

OnCancel()

Question # 2 of 10 ( Start time: 08:44:25 PM ) Total Marks: 1

Consider the following C# code segment: `button.Background = (Brush) new BrushConverter().ConvertFrom ("SystemColors.WindowBrush");` Which one of the following is equivalent XAML code?

Select correct option:

**<Button Background= "SystemColors.WindowsBrush"/>**

<Button Background= "SystemColor.WindowsBrush"/>

<Button Background= "SystemColor.WindowBrush"/>

<Button Background= "SystemColors.WindowBrush"/>

Question # 3 of 10 ( Start time: 08:45:51 PM ) Total Marks: 1

Multi touch events are categorized into \_\_\_\_\_ and \_\_\_\_\_.

Select correct option:

Touch events, touchup events

Touchdown events, touchup events

Advanced touch events, low-level manipulation events

**Basic touch events, higher-level manipulation events**

Question # 4 of 10 ( Start time: 08:46:26 PM ) Total Marks: 1

Which of the following components generates an input Event?

Select correct option:

Printer

**Multi Touch**

Plotter

Speaker

Question # 5 of 10 ( Start time: 08:47:00 PM ) Total Marks: 1

Using \_\_\_\_\_ requires more overhead than \_\_\_\_\_ because of the extra tracking.

Select correct option:

StaticResource, DynamicResource

**DynamicResource, StaticResource**

PermanentResource, TemporaryResource

TemporaryResource, PermanentResource

Question # 6 of 10 ( Start time: 08:47:56 PM ) Total Marks: 1

We use "UIElement" property `ClipToBounds= "false"` when \_\_\_\_\_.

Select correct option:

We want area child element don't cross the boundary of parent

None of given

**We want area of child element is allowed to cross the boundary of parent**

Parent area also increases on increasing of area of child element

Question # 7 of 10 ( Start time: 08:49:22 PM ) Total Marks: 1

The Java programming language has a specific class for creating splash screens, called \_\_\_\_\_.

Select correct option:

Java.awt.start

Java.lang.splash

Java.start.screen

Java.awt.SplashScreen

Question # 8 of 10 ( Start time: 08:50:33 PM ) Total Marks: 1

\_\_\_\_\_ is used to perform navigation.

Select correct option:

Session

Hyperlink

Hypertext markup language code

Internet protocol

Question # 9 of 10 ( Start time: 08:51:28 PM ) Total Marks: 1

Which of the following operation cannot be performed by using a View?

Select correct option:

Grouping

Filtering

Sorting

Searching

Question # 10 of 10 ( Start time: 08:52:36 PM ) Total Marks: 1

To design a complex Interface, which of the following technique is best to achieve the required results?

Select correct option:

Panels composed in three panels

Panels composed within panels

Panels composed in two panels

Panels composed in single panel

Question # 1 of 10 ( Start time: 08:18:20 PM ) Total Marks: 1

Which of the following is not a string format property throughout WPF?

Select correct option:

ContentStringFormat

ItemStringFormat

RowHeaderStringFormat

StringFormat

Question # 2 of 10 ( Start time: 08:19:31 PM ) Total Marks: 1

In multi touch events, a/an \_\_\_\_\_ id is assigned to each individual event.

Select correct option:

Device

Processor

CPU

Event

Question # 3 of 10 ( Start time: 08:20:03 PM ) Total Marks: 1

Commonly we have two types of custom command bindings named as \_\_\_\_\_.

Select correct option:

- StartBindings and StopBindings
- EventBindings and InstanceBindings
- ButtonBindings and TextboxBindings
- KeyBindings and MouseBindings**

Question # 4 of 10 ( Start time: 08:21:16 PM ) Total Marks: 1

Which of the following is an example of tunnel key event?

Select correct option:

- Key up
- Preview key entered
- Preview key down**
- Key down

Question # 5 of 10 ( Start time: 08:22:32 PM ) Total Marks: 1

In context of data binding, \_\_\_\_\_ contains the current item to get it synchronized with data source.

Select correct option:

- String
- Template
- View
- List**

Question # 6 of 10 ( Start time: 08:24:12 PM ) Total Marks: 1

Multi touch events are categorized into \_\_\_\_\_ and \_\_\_\_\_.

Select correct option:

- Touch events, touchup events
- Touchdown events, touchup events
- Advanced touch events, low-level manipulation events
- Basic touch events, higher-level manipulation events**

Question # 7 of 10 ( Start time: 08:25:34 PM ) Total Marks: 1

Which function is used to create cancel button event of dialog box \_\_\_\_\_.

Select correct option:

- OnInitCancel()
- OnClickCancel()**
- CancelClick()
- OnCancel()

Question # 8 of 10 ( Start time: 08:26:59 PM ) Total Marks: 1

\_\_\_\_\_ and \_\_\_\_\_ are the two important properties of Binding object.

Select correct option:

- Start, Destination
- Items, Selected
- Source, Path**
- BindTo, BindFrom

Question # 9 of 10 ( Start time: 08:28:29 PM ) Total Marks: 1

Which one of the following panels is most powerful, versatile and customizable?

Select correct option:

**Grid Panel**

Canvas panel

Doc panel

Stack panel

Question # 10 of 10 ( Start time: 08:29:03 PM ) Total Marks: 1

An event that is raised whenever the value of "CanExecute" changes is known as \_\_\_\_\_.

Select correct option:

CanExecute

**CanExecuteChanged**

Command

Execute

Question # 10 of 10 ( Start time: 09:46:15 PM ) Total Marks: 1

In order to resize the row and column in Grid panel, \_\_\_\_\_ is used.

Select correct option:

Grid divider

Grid compiler

Grid converter

**Grid splitter**

Which of the following is an example of tunnel key event?

Select correct option:

Key up

Preview key entered

**Preview key down**

Key down

Question # 2 of 10 ( Start time: 09:04:53 PM ) Total Marks: 1

Data binding is about tying together arbitrary .NET \_\_\_\_\_.

Select correct option:

**Objects**

Functions

Properties

Variables

Question # 5 of 10 ( Start time: 09:06:36 PM ) Total Marks: 1

\_\_\_\_\_ supports the creation of applications that run directly in a web browser.

Select correct option:

**WPF**

C/C++

C#

HTML

Question # 6 of 10 ( Start time: 09:07:13 PM ) Total Marks: 1

Which of the following operation cannot be performed by using a View?

Select correct option:

Grouping

Filtering

Sorting

Searching

Question # 7 of 10 ( Start time: 09:07:41 PM ) Total Marks: 1

\_\_\_\_\_ is used to perform navigation.

Select correct option:

Session

Hyperlink

Hypertext markup language code

Internet protocol

In context of data binding, \_\_\_\_\_ contains the current item to get it synchronized with data source.

Select correct option:

String

Template

View

List

\_\_\_\_\_ and \_\_\_\_\_ are the two important properties of Binding object.

Select correct option:

Start, Destination

Items, Selected

Source, Path

BindTo, BindFrom

Question # 8 of 10 ( Start time: 09:08:10 PM ) Total Marks: 1

To check that the user either pressed left Alt key or right Alt key, the \_\_\_\_\_ is used.

Select correct option:

IsKeyDown

IsDown

keyboardDevice.IsKeyDown

KeyStates.IsKeyDown

Question # 10 of 10 ( Start time: 09:11:06 PM ) Total Marks: 1

In \_\_\_\_\_ browser app, you change "<TargetZone>Internet</TargetZone>" to "<TargetZone>Custom</TargetZone>"

Select correct option:

Partial-trust

Full-reject

Partial-reject

Full-trust

Question # 1 of 10 ( Start time: 09:13:52 PM ) Total Marks: 1

\_\_\_\_\_ provides the logic behind the "Back" and "Forward" buttons.

Select correct option:

- Hyperlink
- Navigation Window
- IFrame
- Journal**

Question # 7 of 10 ( Start time: 10:08:33 PM ) Total Marks: 1

In multi touch events, when multiple fingers are touching simultaneously, these events get raised for each finger \_\_\_\_\_.

Select correct option:

- Independently**
- Completely
- Partially
- Dependently

Question # 9 of 10 ( Start time: 10:09:30 PM ) Total Marks: 1

In a code segment, if the Visibility="Collapsed" then which of the following events are not generated?

Select correct option:

- Key down Events
- Mouse Events**
- Routed Events
- Keyboard Events

Question # 7 of 10 ( Start time: 10:17:09 PM ) Total Marks: 1

A Window can spawn \_\_\_\_\_ number of additional Windows by instantiating a Window-derived class and calling Show(...).

Select correct option:

- Four
- Any**
- Six
- Five

Question # 3 of 10 ( Start time: 10:22:29 PM ) Total Marks: 1

Frame has a \_\_\_\_\_ property used in enabling or disabling the bar.

Select correct option:

- ShowsNavigationUI
- BlocknavigationUI
- NavigationUIVisibility**
- NavigationUIBlock

Question # 4 of 10 ( Start time: 10:23:10 PM ) Total Marks: 1

If we insert some objects in a single cell in Grid panel, then these objects are placed on \_\_\_\_\_

Select correct option:

- One on Top of the other**
- One after the other
- One on Bottom of the other

One on Side of the other

Question # 6 of 10 ( Start time: 10:24:01 PM ) Total Marks: 1

A \_\_\_\_\_ receives keyboard events only if it has keyboard focus.

Select correct option:

Mouse

Keyboard Controls

Keyboard

UIElement

Question # 1 of 10 ( Start time: 09:53:44 PM ) Total Marks: 1

To remove data binding between the source and the target, we can use \_\_\_\_\_ function.

Select correct option:

ClearBinding

ResetBinding

StopBinding

RemoveBinding

Question # 2 of 10 ( Start time: 09:54:31 PM ) Total Marks: 1

A/An \_\_\_\_\_ screen is an image that appears while a game or program is loading

Select correct option:

Opening

Initial

Splash

Startup

Question # 3 of 10 ( Start time: 09:54:52 PM ) Total Marks: 1

We can perform sorting through View by using an object of \_\_\_\_\_ class.

Select correct option:

ViewOrder

ViewDescription

SortOrder

SortDescription

Question # 4 of 10 ( Start time: 09:55:44 PM ) Total Marks: 1

"Binding" technique binds two properties together and keeps a \_\_\_\_\_ open.

Select correct option:

Memory location

Selection

Choice

Communication channel

Which one of the following can be used to set dependency property values?

Select correct option:

Temporary resource

Permanent resource

Dynamic resource

Static resource

Question # 6 of 10 ( Start time: 09:56:53 PM ) Total Marks: 1

\_\_\_\_\_ is used to perform navigation.

Select correct option:

Session

**Hyperlink**

Hypertext markup language code

Internet protocol

Question # 7 of 10 ( Start time: 09:57:13 PM ) Total Marks: 1

Which one of the following is used, if we want to add a window resource in procedural code?

Select correct option:

Window.Resource.Add ();

<Widows.Resources></Widows.Resources>

**Window.Resoruces.Add();**

<Window.Resources></Window.Resources>

Question # 8 of 10 ( Start time: 09:57:49 PM ) Total Marks: 1

We use "GetDefaultView" method of \_\_\_\_\_ to get the default View.

Select correct option:

CollectionViewSource

DataSource

ViewDescription

ViewCollection

Question # 8 of 10 ( Start time: 09:57:49 PM ) Total Marks: 1

We use "GetDefaultView" method of \_\_\_\_\_ to get the default View.

Select correct option:

**CollectionViewSource**

DataSource

ViewDescription

ViewCollection

Question # 9 of 10 ( Start time: 09:58:54 PM ) Total Marks: 1

In case of HTML page navigation, you must use the \_\_\_\_\_ of "Navigate" that \_\_\_\_\_ a URI.

Select correct option:

Overload, rejects

IFrame, rejects

IFrame, accepts

**Overload, accepts**

Question # 10 of 10 ( Start time: 10:00:08 PM ) Total Marks: 1

The Java programming language has a specific class for creating splash screens, called \_\_\_\_\_.

Select correct option:

Java.awt.start

Java.lang.splash

Java.start.screen

**Java.awt.SplashScreen**



Question # 8 of 10 ( Start time: 10:42:41 PM ) Total Marks: 1

In case of integrating Navigation to XBAP, "ShowNavigationUI" should be set to \_\_\_\_\_ in order to bypass integration.

Select correct option:

**False**

True

Null

0

AIRBORNE